

345 Carlingview Drive Toronto, Ontario CANADA M9W 6N9 Tel.: 416.734.3300

Fax.: 416.231.1626 Toll Free: 1.877.682.8772

www.tssa.org

January 10, 2018

SUSAN TURNER
PARKER HANNIFIN INSTRUMENTATION GROUP CANADA
4635 DURHAM RD S
GRIMSBY ON L3M 4G4
CA

Service Request Type.: BPV-National MB

Service Request No.: 2134448 Your Reference No.: MPI RENEWAL

Registered to.: PARKER HANNIFIN - INSTRUMENTATION PRODUCTS DIVISION

Dear SUSAN TURNER.

Please find enclosed the original response from MB, registered under the CRN No.: 0A11716.54.

As all jurisdictional fees are handled by the Technical Standards and Safety Authority (TSSA), you do not pay any jurisdictions directly.

Should you have any questions or require further assistance, I will be happy to assist you. For general enquiries, please contact a Customer Service Advisor at 1.877.682.TSSA (8772) or e-mail customerservices@tssa.org. When contacting TSSA regarding this file, please refer to the Service Request number provided above.

Yours truly,

Tanya Francis Administrative Assistant_ BPV Engineering

Tel.: 416-734-3423 Fax: 416-231-6183 Email:tfrancis@tssa.org



Inspection and Technical Services Manitoba 500 - 401 York Avenue

Winnipeg Manitoba R3C 0P8
T (204) 945-3373
F (204) 948-2309
www.firecomm.gov.mb.ca/codes_steam_pressure.html

November 29, 2017

TSSA 345 Carlingview Drive Toronto, ON M9W 6N9

Attn: Tanya Francis

REGISTRATION OF VALVES AND FITTINGS

Manufacturer: Parker Hannifin - Instrumentation Products Division

The design(s) for the following Valves/Fittings has been received by us and has been examined and accepted for registration in the Province of Manitoba as follows.

DRAWING / CATALOGUE	CRN	FILE
Catalog 4234 (April 2015) Pages 13 through 32	0A11716.54	38235

An invoice covering survey and registration fees is enclosed.

NOTE:

- CRN registered under reciprocal agreement & is conditional based on compliance with the notes set by the original issuing Jurisdiction: ABSA
- See attached stamped "this is part of CRN" for scope of registration.
- This registration expires July 24, 2027.

This registration is valid until the indicated expiry date only if the Manufacturer maintains a valid quality management system approved by an acceptable third-party agency until that date. Should the approval of the quality management system lapse before the expiry date indicated above, this registration shall become void.

The registration of this design does not relieve the manufacturer, the owner or his agent of the responsibility for the design or construction of a fitting in accordance with the applicable Acts, Codes and Standards. Inspection and Technical Services assumes no responsibility by registering designs, examining plans and/or inspecting equipment or facility.

Yours truly,

Rabie Harb, E.I.T.

Design Surveyor

Office of the Fire Commissioner

Inspection and Technical Services Manitoba

508 - 401 York Avenue

Winnipeg, Manitoba, R3C 0P8

Phone: 204-945-3373

Email: rabie.harb@gov.mb.ca



Parker Hannifin Corporation Instrumentation Products Division 1005 A Cleaner Way Huntsville, AL 35805 Office 256-881-2040 Fax 256-881-5072

April 10, 2017



Apr. 1 10, 2017

SCOPE OF REGISTRATION RENEWAL 0A11716.5

The scope of this registration renewal are the fittings, Size 4, 6, 8, and 9, listed on pages 13 through 32 of Catalog 4234, Medium Pressure Products, dated April 2015. These are the same fittings as were covered by the existing registration. The design of these fittings has not changed since the original registration. A change was made to previous catalog offerings to add an additional material, as described below. This addition was process as an addendum to the previous registration 0A11716.5ADD1 and is recreated below for inclusion in this renewal.

Super Duplex 2507 (UNS 32750) stainless steel has been added to the possible materials of construction for the MPI line of fittings (Sizes 4, 6, 8, & 9). The existing registration for the MPI line of fittings is based on calculations and supplemental burst tests using Type 316 stainless steel materials as listed in the existing registration (shown below):

Spec	Material Designation	Hex	Tensile	Yield	Stress
SS-60	ASME-SA-479, Type 316	1 1/4"	100Ksi	80Ksi	33.3Ksi
SS-85	ASME-SA-479, Type 316/316L	1 1/4"	100Ksi	80Ksi	33.3Ksi
SS-63	ASTM-A-276, Type 316	1 3/4"(1)	125Ksi	105Ksi	41.6Ksi
SS-91	ASME-SA-213 & 269, Type 316	1"(2)	105Ksi	70Ksi	35.0Ksi

- (1) rectangular bar stock
- (2) 1/8 hard tubing

The additional new material is:

Spec	Material Designation	<u>Hex</u>	Tensile	Yield	Stress
SS-15	ASTM- A-479, UNS 32750	1 1/4"	116Ksi	80Ksi	38.7Ksi
SS-15	ASTM- A-479, UNS 32750	1 3/4"(1)	116Ksi	80Ksi	38.7Ksi

(1) rectangular bar stock

Parts made from this alternate material would have no changes to the form, fit, function, configuration or dimensions from those used in parts made from the Type 316 stainless steel listed in the original registration. The calculations is the original registration were based on the lowest allowable stress for the material listed in catalog as shown above. The allowable stress for the alternate material is greater than the lowest used in all the calculations in the original registration.

Fredrick Rov. P.E.

Project Engineer - Quality Certifications, Registrations

and Nuclear Products



TECHNICAL STANDARDS & SAFETY AUTHORITY 14th Floor, Centre Tower 3300 Bloor Street West Toronto, Ontario Canada M8X 2X4 Show facsimile of manufacturer's logo or trademark, as it will appear on the fitting, in the space below

see attached

STATUTORY DECLARATION Registration of Fittings Tony Wyszkowski, General Manager (Name and Position, e.g. President, Plant Manager, Chief Engineer) of Parker Hannifin, Instrumentation Products Division (Name of Manufacturer) Located at 1005 A Cleaner Way, Huntsville, AL 256-881-2040 256-881-5072 (Plant Address) (Telephone No.) (Fax No.) do solemnly declare that the fittings listed hereunder, which are subject to the Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, comply with all of the requirements of (Title of recognized North American Standard) which specifies the dimensions, materials of construction, pressure/temperature ratings, identification marking the fittings and service; ✓ or are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with ASME B31.3 as supported by the attached data which identifies the dimensions, material of construction, pressure/temperature ratings and the basis for such ratings, the marking of the fitting for identification and service. I further declare that the manufacture of these fittings is controlled by a quality system meeting the requirements of ISO 9001:2008 which has been verified by the following authority, Det Norske Veritas The items covered by this declaration, for which I seek registration, are category A _ type fittings. In support of this application, the following information and/or test data are attached as follows: Scope of Registration Renewal 0A11716.5, Design Report, Material specification ES-242, Catalog 4234 - April 2015 (drawings, calculations, test reports, etc.) Declared before me at Huntsville, Madison County in the State day of april AD 20 17 Commissioner for Oaths: Aheri Cocase (Signature) (Signature of Declarer) FOR OFFICE USE ONLY To the best of my knowledge and belief, the application meets the requirements of the Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, and CSA Standard B51 and is accepted for registration in Category CRN: Registered by: Dated:

NOTE: This registration expires on:



Parker Engineering Manual Parker Hannifin Corporation

Parker Hannifin Corporation Instrumentation Connectors Division

Issued 6-25-79	Section IDENTIFICATION
Revised	Standard No.
1-15-98	ES-703
Ecn No.	Page
ICD97055	1 OF 6
Parker Symbol	

Sul	oje	ct:
-----	-----	-----

PRODUCT LOGO MARKING REQUIREMENTS

Parker Symbol

ID-3

GENERAL:

The following information is adapted from Parker's Corporation Communications and Identification Manual.

PRODUCT IDENTIFICATION:

It is important that Parker identification appear on the millions of components sold into the market place each year. For this reason, special versions of the Corporate Signature have been designed to accommodate difficult product marking situations. The three key variables which will govern the selection of proper identification techniques are the material on which the marking is to be applied, the surface contour, and identification area size. The order of preference for product marking usage is shown. When possible, the solid Signature should be used down to a minimum of 5/8 inch. For smaller applications, the solid Open Signature, with slightly more open space within the letterforms, should be used. The Linear Signature and the Helvetica Light Parker are approved only for especially difficult marking conditions and hard material surfaces. When the marking surface, contour or area size makes it impractical to use the complete Parker identification, a "P" may be used in order of preference shown. Critical dimensions for product identification only are provided in this section.



Parker Engineering Manual

Parker Hannifin Corporation Instrumentation Connectors Division

Issued 6-25-79	Section IDENTIFICATION	
Revised 1-15-98	Standard No. ES-703	
Ecn No. ICD97055	Page 2 OF 6	

Subject:

PRODUCT LOGO MARKING REQUIREMENTS

Parker Symbol

ID-3

1 Primary
Corporate Signature
Minimum Size 5/8"



2 Small Size Corporate Signature Maximum Size 5/8"



3 Linear Corporate Signature



4 Straight Type Identification— Helvetica Light

Parker

5 Small Size "P"
Maximum Size 1/16"



6 Linear "P"



7 Straight Type "P" Identification— Helvetica Light

P . : ننټز