UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUNAVUT	NOVA SCOTIA YUKON	PRINCE EDWARD ISLAND NORTHWEST TERRITORIES	NEWFOUNDLAND AND LABRADOR		
MANUFACTURERS NAME:	Parker Hannifin Corp	oration Instrumentation Products Division			
MANUFACTURERS ADDRESS:	1005 A Cleaner Way, Huntsville, Alabama, 35805, USA				
PLANT LOCATIONS:					
CATEGORY OF FITTIN	NGS TO BE REGISTER	RED, CIRCLE ONE CATEGORY ONLY	TITLE OF THE STANDARD OF CONSTRUCTION		
Franges: all flanges Valves: all fine valves Expansion joints, flexible conni E Strainers, filters, separators, ar Measuring devices, including p pressure transmitters	ections, and hose asset not steam traps pressure gauges, level g are relief devices accept no and fusible plucs	auges, sight glasses, levels, or able as primary over pressure protection on	Manufactured to comply with ASME B31.3		
N Nuclear components: Class 1	Class 2 Class 3	(Meeting CNSC or ASME requirements)			
		OGO AS IT WILL APPEAR ON THE PRODUC	T TYPE OF CONSTRUCTION		
		Hached.	FORGED D WELDED D WROUGHT D CAST D OTHER D DESCRIBE OTHER		
LIST OF SUPPORTING DOCUME	ENTATION AND IDENT	TELCATION OF THE ACTUAL ITEMS TO BE	REGISTERED:		
Scope of Registration Renewal DA	11716.5. Design Repor	rt, Material Specification ES-22, Catalog 4234	April 2015		
ly knowledge represents the promperature ratings, and identific anufacture of these fittings is re- in part and has been verified b	e end product do soli oduct for which regist cation markings are in egulated by a Quality by DNV - GL	ed by Parker Hannifin Corporation and be empty declare that the information contain tration is sought. The dimensions, materian accordance with the herein named stands Control Program which extends to each as being suitable for the control of the	ned in this form is true and to the best of als of construction, pressure dards. I further declare that the polant where fabrication occurs in whole		
gnature of Declarer:	dula Maria	knowing that it is of the same force and e			
eclared before me at Hunt	stille, Madi	son County USETHIS	S SPALE TO		
his 28th day of a	elf() AD ?	1017 OFF	ICIAL SCAL TYA		
ommissioner of Oaths	^		1 1 1		
Notary Public: (sign)	resu Cogge		11 (원 년		
This regi		space for Regulatory Authority use alidated after ten (10) years from the date	of acceptance.		
CRN: DA11716.5 Rev		• • • • • • • • • • • • • • • • • • • •	Newforth fland		
1027			Labrador		
ID#:			Service NL		
lotes: . All fittings shall be registered in ti	the name of the Manufa	cturer.	Registered OA 11716. 50 kg 2 Date 17/08/25,		
 Each category shall be supported orms and one copy of supporting do 	d with two Statutory Dec	claration	Engineering and Inspection Services		
 The declaration shall be made by 	v the person having full				
esponsibility for the quality of the er . Quality control programs shall be		authority and	Registered by h.		
	nd product.		UNDER THE AUTHORITY OF THE PUBLIC SAFETY ART AND		



Parker Engineering Manual

Parker Hannifin Corporation
Instrumentation Connectors Division

Issued	Section
6-25-79	IDENTIFICATION
Revised	Standard No.
1-15-98	ES-703
Ecn No.	Page
ICD97055	1 OF 6
Parker Symbol	

Subject:					
	Sı	ıh	ie	cf	

PRODUCT LOGO MARKING REQUIREMENTS

ID-3

GENERAL:

The following information is adapted from Parker's Corporation Communications and Identification Manual.

PRODUCT IDENTIFICATION:

It is important that Parker identification appear on the millions of components sold into the market place each year. For this reason, special versions of the Corporate Signature have been designed to accommodate difficult product marking situations. The three key variables which will govern the selection of proper identification techniques are the material on which the marking is to be applied, the surface contour, and identification area size. The order of preference for product marking usage is shown. When possible, the solid Signature should be used down to a minimum of 5/8 inch. For smaller applications, the solid Open Signature, with slightly more open space within the letterforms, should be used. The Linear Signature and the Helvetica Light Parker are approved only for especially difficult marking conditions and hard material surfaces. When the marking surface, contour or area size makes it impractical to use the complete Parker identification, a "P" may be used in order of preference shown. Critical dimensions for product identification only are provided in this section.



Parker Engineering Manual Parker Hannifin Corporation

Parker Hannifin Corporation Instrumentation Connectors Division

Issued	Section	
6-25-79	IDENTIFICATION	
Revised	Standard No.	
1-15-98	ES-703	
Ecn No.	Page	
ICD97055	2 OF 6	

Subject:

PRODUCT LOGO MARKING REQUIREMENTS

Parker Symbol

ID-3

1 Primary
Corporate Signature
Minimum Size 5/8"



2 Small Size Corporate Signature Maximum Size %"



3 Linear Corporate Signature



4 Straight Type Identification— Helvetica Light Parker

5 Small Size "P" Maximum Size 3/16"



6 Linear "P"



7 Straight Type "P" Identification—
Helvetica Light

Р

altana a a a a a a a a