UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUNAVUT	NOVA SCOTIA YUKON	PRINCE EDW. NORTHWEST	ARD ISLAND TERRITORIES	NEWFOUNDLAND AND LABRADOR	
MANUFACTURERS NAME:	Parker Hannifin Corpora	tion Instrumentation I	entation Products Division		
MANUFACTURERS ADDRESS:	1005 A Cleaner Way, Huntsville, Alabama, 35805, USA				
PLANT LOCATIONS:					
	GS TO BE REGISTERED	O. CIRCLE ONE CAT	EGORY ONLY	TITLE OF THE STANDARD OF CONSTRUCTION	
A Pipe fittings, including coupling B Flanges: all flanges C Valves: all line valves D Expansion joints, flexible conne E Strainers, filters, separators, and	s, tees, elbows, Ys, plugs ections, and hose assemb d steam traps	, unions, pipe caps, o	r reducers	Manufactured to comply with ASME B31.3	
Measuring devices, including progressure transmitters Certified capacity-rated pressure boilers, pressure vessels, pipin	e relief devices acceptable	e as primary over pre	ssure protection on		
H Pressure retaining components	that do not fall into one of	the above categories	i		
N Nuclear components: Class 1 I	☐ Class 2 ☐ Class 3 ☐,	(Meeting CNSC or A	SME requirements)		
SHOW MANUFACTURERS NAME			AR ON THE PRODU	FORGEO WELDED WROUGHT CAST OTHER DESCRIBE OTHER	
	see at	tached.			
LIST OF SUPPOPTING BOOKING	AITATION AND ISSUE				
LIST OF SUPPORTING DOCUME Scope of Registration Renewal 0A	11716.5, Design Report, N	Material Specification	ES-22, Catalog 4234	- April 2015	
emperature ratings, and identific	duct for which registral ation markings are in a gulated by a Quality Ct DNV - GL ing it to be true and kn	inly declare that the tion is sought. The ccordance with the pontrol Program which as nowing that it is of the country	e information contai dimensions, mater herein named stan ch extends to each s being suitable for he same force and U.S.E. T.H.I.	plant where fabrication occurs in whole	
This ropid	This sp	ace for Regulatory Au	thoray use	NOWAVOT	
CRN: OAll716.5 Rev	stration must be revalid		115 DC	Pressure Vessels Act	
1027	_	Nu			
FID#:		1	REG	ISTERED	
Notes: All fittings shall be registered in the second of the supported orms and one copy of supporting do. The declaration shall be made by esponsibility for the quality of the en. Quality control programs shall be to a maximum interval of five (5) year	with two Statutory Declar cumentation. the person having full aut d product. resubmitted for validation	hority and Sign	DA117	16. SN Revo	
			Territorial F	Registration Fee	
				The same of the sa	



Parker Engineering Manual

Parker Hannifin Corporation
Instrumentation Connectors Division

Issued	Section
6-25-79	IDENTIFICATION
Revised	Standard No.
1-15-98	ES-703
Ecn No.	Page
ICD97055	1 OF 6
Parker Symbol	

Sı	ıh	ie	cf	•

PRODUCT LOGO MARKING REQUIREMENTS

ID-3

GENERAL:

The following information is adapted from Parker's Corporation Communications and Identification Manual.

PRODUCT IDENTIFICATION:

It is important that Parker identification appear on the millions of components sold into the market place each year. For this reason, special versions of the Corporate Signature have been designed to accommodate difficult product marking situations. The three key variables which will govern the selection of proper identification techniques are the material on which the marking is to be applied, the surface contour, and identification area size. The order of preference for product marking usage is shown. When possible, the solid Signature should be used down to a minimum of 5/8 inch. For smaller applications, the solid Open Signature, with slightly more open space within the letterforms, should be used. The Linear Signature and the Helvetica Light Parker are approved only for especially difficult marking conditions and hard material surfaces. When the marking surface, contour or area size makes it impractical to use the complete Parker identification, a "P" may be used in order of preference shown. Critical dimensions for product identification only are provided in this section.



Parker Engineering Manual Parker Hannifin Corporation

Parker Hannifin Corporation Instrumentation Connectors Division

Issued	Section		
6-25-79	IDENTIFICATION		
Revised	Standard No.		
1-15-98	ES-703		
Ecn No.	Page		
ICD97055	2 OF 6		

Subject:

PRODUCT LOGO MARKING REQUIREMENTS

Parker Symbol

ID-3

1 Primary
Corporate Signature
Minimum Size 5/8"



2 Small Size Corporate Signature Maximum Size %"



3 Linear Corporate Signature



4 Straight Type Identification— Helvetica Light Parker

5 Small Size "P" Maximum Size 3/16"



6 Linear "P"



7 Straight Type "P" Identification—
Helvetica Light

Р

altana a a a a a a a a