G 1 1/4
G 3/4
G 3/8
G 1/8

Europe

Series 27	Series 25/26	Series 21	Series 20
DN 10	DN 7.8	DN 5	DN 2.7

ISO C

Series 84	Series 18	Series 303
DN 5.5	DN 5.5	DN 3

UK

Series 19	Series 17
DN 5.5	DN 5

Asia

Series 13
DN 7.5

G 1/8
G 3/8
G 3/4
G 1 1/4

0cm 1 2 3 4 5

Parker

RECTUS

legris

Aro

Series 22
DN 5.5

ISO 6150 B

Series 24/1400	Series 30	Series 37
DN 5.5	DN 8.5	DN 11

Atlas Copco

Series 33	Series 34
DN 8	DN 10

Walther

Series 51	Series 52	Series 57
DN 6	DN 6	DN 12

M5 x 0.8
G 1/4
G 1/2
G 1

G 1/4
G 1/2
G 1

G 1/4
G 1/2
G 1

www.parker.com/LPCE

G 1/8
G 3/8
G 3/4
G 1 1/4

AVAILABLE SAFETY FEATURES

- **KR** Straight-Through
- **KS** Single Shut-Off
- **KD** Double Shut-Off
- **KE** Self-Venting System Sleeve Design
- **KP** Self-Venting System Push-Button
- **KS** Breathing Air

SHUT-OFF VERSIONS

- **KF** Straight-Through
- **KA** Single Shut-Off
- **KB** Double Shut-Off
- **KL** Dry-Break

MATERIALS / SEALS

Brass

Steel

Stainless Steel

Thermoplastic

NBR / FKM / EPDM / FFKM

COUPLER PERFORMANCES

Temperature: up to +200°C

Pressure: up to 60 bar

Flow: up to 17.000 l/min.

M5 x 0.8
G 1/4
G 1/2
G 1

G 1/8
G 3/8
G 3/4
G 1 1/4